



# SAFETY DATA SHEET

US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date 01-Nov-2022

Revision Date -

Revision Number 1

## 1. Identification

### Product identifier

**Product Name** Premium Glossy Paint Marker (non-metallic colors)

### Other means of identification

**Product Code(s)** 10201B Black, 10204B Red, 10205B White

**UN/ID no** UN1210

**Synonyms** Premium Glossy Paint Marker

### Recommended use of the chemical and restrictions on use

**Recommended use** Paint Markers

**Restrictions on use** Keep away from children. Not to be used for skin.

### Details of the supplier of the safety data sheet

#### Supplier Address

U-Mark, Inc  
102 Iowa Ave.  
Belleville, IL 62220  
TEL: 618-235-7500

#### Emergency telephone number

**Emergency telephone** 24-hour Emergency Phone: Infotrac 1-800-535-5053 (USA & Canada), 1-352-323-3500 (International)

## 2. Hazard(s) identification

### Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

### Label elements

**Warning**

**Hazard statements**

Flammable liquid and vapor.  
 Harmful if inhaled.  
 Causes serious eye irritation.  
 May cause drowsiness or dizziness.



**Precautionary Statements - Prevention**

Avoid breathing dust, fume, gas, mist, vapors and spray. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed. Ground and bond container and receiving equipment. Wear protective gloves/protective clothing. Use only non-sparking tools. Take action to prevent static discharges. Wear protective gloves, eye protection and face protection. Keep cool.

**Precautionary Statements - Response**

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and then shower.

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

**Fire**

In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to extinguish.

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Precautionary Statements - Disposal**

Dispose of contents and container to an approved waste disposal plant.

**Other information**

Harmful to aquatic life.

**3. Composition/information on ingredients**

**Substance**

Not applicable.

**Mixture**

**Synonyms** Premium Glossy Paint Marker

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Ethyl acetate	141-78-6	30-48	-	-

Propylene glycol monomethyl ether acetate	108-65-6	14.24-33.24	-	-
Titanium dioxide	13463-67-7	1.8-25.2	-	-
Non Hazardous Component		8.6	-	-
Carbon black	1333-86-4	0.5-7	-	-
Iron oxide	1309-37-1	6.5	-	-
3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)] bis[2,4-dihydro-5-methyl-2-phenyl-	3520-72-7	0-5	-	-
4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bi s[2,4-dihydro-5-methyl-2-(p-tolyl)-3H-pyrazol-3-one]	15793-73-4	1-5	-	-
C.I. Pigment Blue 15	147-14-8	2	-	-
Silicon dioxide	7631-86-9	1.02-1.68	-	-
Aluminum hydroxide	21645-51-2	1.12	-	-
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl	5468-75-7	0-0.5	-	-
Copper	7440-50-8	0.22	-	-
Xylene	1330-20-7	0.2	-	-
Quartz	14808-60-7	0.12	-	-

## 4. First-aid measures

### Description of first aid measures

<b>General advice</b>	Under normal conditions of use first aid is not required. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Remove to fresh air. IF exposed or concerned: Get medical advice/attention. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists.

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing. Difficulty in breathing.
-----------------	--

### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

## 5. Fire-fighting measures

---

<b>Suitable Extinguishing Media</b>	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	The ink contained in this product is flammable but not readily ignited. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	None.
<b>Sensitivity to static discharge</b>	Yes.
<b>Special protective equipment and precautions for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapors or mists.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

### Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## 7. Handling and storage

### Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep out of the reach of children.

**8. Exposure controls/personal protection**

Control parameters

**Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH	
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>	
Titanium dioxide 13463-67-7	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale	
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
Iron oxide 1309-37-1	TWA: 5 mg/m <sup>3</sup> respirable particulate matter	TWA: 10 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> fume and total dust Iron oxide (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction regulated under Rouge	IDLH: 2500 mg/m <sup>3</sup> Fe dust and fume TWA: 5 mg/m <sup>3</sup> Fe dust and fume	
C.I. Pigment Blue 15 147-14-8	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	-	IDLH: 100 mg/m <sup>3</sup> Cu dust and mist TWA: 1 mg/m <sup>3</sup> Cu dust and mist	
Silicon dioxide 7631-86-9	-	-	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>	
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m <sup>3</sup> respirable particulate matter	-	-	
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume	
Xylene 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-	
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust	
Chemical name	Alberta	British Columbia	Ontario	Quebec
Ethyl acetate 141-78-6	TWA: 400 ppm TWA: 1440 mg/m <sup>3</sup>	TWA: 150 ppm	TWA: 400 ppm	TWA: 400 ppm TWA: 1440 mg/m <sup>3</sup>
Propylene glycol monomethyl ether acetate	-	TWA: 50 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 270 mg/m <sup>3</sup>	-

108-65-6				
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
Iron oxide 1309-37-1	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
Aluminum hydroxide 21645-51-2	-	TWA: 1.0 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	-
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Xylene 1330-20-7	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>

**Biological occupational exposure limits**

Chemical name	ACGIH
Xylene 1330-20-7	1.5 g/g creatinine - urine (Methylhippuric acids) - end of shift

**Appropriate engineering controls**

**Engineering controls**                      Showers  
    Eyewash stations  
    Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**                      Tight sealing safety goggles.

**Hand protection**                            Wear suitable gloves. Impervious gloves.

**Skin and body protection**                Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

**Respiratory protection**                    No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations**        Do not eat, drink or smoke when using this product. Contaminated work. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

**9. Physical and chemical properties**

**Information on basic physical and chemical properties**

**Appearance**                                    colored, opaque liquid  
**Physical state**                                Liquid  
**Color**    Varies  
**Odor**     Hydrocarbon-like  
**Odor threshold**                                No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH		No data available
Melting point / freezing point		No data available
Initial boiling point and boiling range	119-207°C / 246.2-404.6°F	(Liquid Ink)
Flash point	<15°C / <59°F	(Liquid Ink)
Evaporation rate		No data available
Flammability		No data available
<b>Flammability Limit in Air</b>		
Upper flammability or explosive limits	7%	
Lower flammability or explosive limits	1%	
Vapor pressure	0.67 - 0.93 kPa (5 - 7 mmHg)	
Vapor density	> 1	(air = 1)
Relative density	0.9	
Water solubility	Insoluble in water	
Solubility(ies)		No data available
Partition coefficient		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available
<b>Other information</b>		
Explosive properties	No information available.	
Oxidizing properties	No information available.	
Softening point	No information available	
Molecular weight	No information available	
VOC content	40-65	
Liquid Density	No information available	
Bulk density	No information available	

**10. Stability and reactivity**

Reactivity	None under normal use conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	None known based on information supplied.

**11. Toxicological information**

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation.

Prolonged contact may cause redness and irritation.

**Ingestion**

Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Symptoms related to the physical, chemical and toxicological characteristics****Symptoms**

May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/or wheezing.

**Acute toxicity****Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (dermal) 13,386.70 mg/kg

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acetate	= 5620 mg/kg ( Rat )	> 18000 mg/kg ( Rabbit )	= 4000 ppm ( Rat ) 4 h
Propylene glycol monomethyl ether acetate	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	= 16000 mg/m <sup>3</sup> ( Rat ) 6 h
Titanium dioxide	> 10000 mg/kg ( Rat )	-	= 5.09 mg/L ( Rat ) 4 h
Carbon black	> 15400 mg/kg ( Rat )	-	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
Iron oxide	> 10000 mg/kg ( Rat )	-	-
3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2,4-dihydro-5-methyl-2-phenyl-	> 5 g/kg ( Rat )	> 2000 mg/kg ( Rat )	-
4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2,4-dihydro-5-methyl-2-(p-tolyl)-3H-pyrazol-3-one]	-	> 2000 mg/kg ( Rat )	-
C.I. Pigment Blue 15	> 10000 mg/kg ( Rat )	> 5000 mg/kg ( Rat )	-
Silicon dioxide	= 7900 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	> 58.8 mg/L ( Rat ) 4 h
Aluminum hydroxide	> 5000 mg/kg ( Rat )	-	-
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl	> 5 g/kg ( Rat )	-	> 230 mg/m <sup>3</sup> ( Rat ) 4 h
Copper	-	-	> 5.11 mg/L ( Rat ) 4 h
Xylene	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Skin corrosion/irritation**

May cause skin irritation.

**Serious eye damage/eye irritation**

Classification based on data available for ingredients. Causes serious eye irritation.

**Respiratory or skin sensitization**

No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	A3	Group 2B	-	X
Carbon black 1333-86-4	A3	Group 2B	-	X
Iron oxide 1309-37-1	-	Group 3	-	-
Silicon dioxide 7631-86-9	-	Group 3	-	-
Xylene 1330-20-7	-	Group 3	-	-
Quartz 14808-60-7	A2	Group 1	Known	X

**Legend**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** May cause drowsiness or dizziness. May cause respiratory irritation.

**STOT - repeated exposure** No information available.

**Target organ effects** Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system. Lungs. Lymphatic System.

**Aspiration hazard** No information available.

**12. Ecological information**

**Ecotoxicity** Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethyl acetate 141-78-6	-	LC50: 220 - 250mg/L (96h, Pimephales promelas) LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus)	-	EC50: =560mg/L (48h, Daphnia magna)

		mykiss)		
Propylene glycol monomethyl ether acetate 108-65-6	-	LC50: =161mg/L (96h, Pimephales promelas)	-	EC50: >500mg/L (48h, Daphnia magna)
Iron oxide 1309-37-1	-	LC50: =100000mg/L (96h, Danio rerio)	-	-
Silicon dioxide 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)
Copper 7440-50-8	EC50: 0.0426 - 0.0535mg/L (72h, Pseudokirchneriella subcapitata) EC50: 0.031 - 0.054mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 0.0068 - 0.0156mg/L (96h, Pimephales promelas) LC50: <0.3mg/L (96h, Pimephales promelas) LC50: =0.2mg/L (96h, Pimephales promelas) LC50: =0.052mg/L (96h, Oncorhynchus mykiss) LC50: =1.25mg/L (96h, Lepomis macrochirus) LC50: =0.3mg/L (96h, Cyprinus carpio) LC50: =0.8mg/L (96h, Cyprinus carpio) LC50: =0.112mg/L (96h, Poecilia reticulata)	-	EC50: =0.03mg/L (48h, Daphnia magna)
Xylene 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)

**Persistence and degradability** No information available.

**Bioaccumulation**

**Component Information**

Chemical name	Partition coefficient
Ethyl acetate	0.73

141-78-6	
Propylene glycol monomethyl ether acetate 108-65-6	1.2
C.I. Pigment Blue 15 147-14-8	6.6
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl 5468-75-7	0.5
Xylene 1330-20-7	3.15

**Mobility in soil** No information available.

**Other adverse effects** No information available.

**13. Disposal considerations**

**Waste treatment methods**

**Waste from residues/unused products** Should not be released into the environment, Dispose of in accordance with local regulations, Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**California waste information** This product contains one or more substances that are listed with the State of California as a hazardous waste.

**14. Transport information**

**DOT**

UN/ID no UN1210  
 Proper shipping name PRINTING INK  
 Transport hazard class(es) 3  
 Packing group III  
 Reportable Quantity (RQ) (Ethylbenzene: RQ (kg)= 454.00, Xylene: RQ (kg)= 45.40, Ethyl acetate: RQ (kg)= 2270.00) Ethylbenzene: RQ (lb)= 1000.00, Xylene: RQ (lb)= 100.00, Ethyl acetate: RQ (lb)= 5000.00  
 Reportable quantity kg Ethylbenzene: RQ (kg)= 3671.00, Xylene: RQ (kg)= 22700.00, Ethyl acetate: RQ (kg)= 4729.00  
 Reportable quantity lbs. Ethylbenzene: RQ (lb)= 8087.00, Xylene: RQ (lb)= 50000.00, Ethyl acetate: RQ (lb)= 10417.00  
 Special Provisions B1, IB3, T2, TP1, 367  
 DOT Marine Pollutant NP  
 Description UN1210, PRINTING INK, 3, III  
 Emergency Response Guide Number 129

**TDG**

UN/ID no UN1210  
 Proper shipping name PRINTING INK  
 Transport hazard class(es) 3  
 Packing group III  
 Special Provisions 59, 142  
 Description UN1210, PRINTING INK, 3, III

**IATA**

UN number or ID number UN1210  
 UN proper shipping name Printing ink  
 Transport hazard class(es) 3

<b>Packing group</b>	III
<b>ERG Code</b>	3L
<b>Special Provisions</b>	A3, A72, A192
<b>Description</b>	UN1210, Printing ink, 3, III

**IMDG**

<b>UN number or ID number</b>	UN1210
<b>UN proper shipping name</b>	PRINTING INK
<b>Transport hazard class(es)</b>	3
<b>Packing group</b>	III
<b>EmS-No</b>	F-E, S-D
<b>Special Provisions</b>	163, 223, 367, 955
<b>Marine pollutant</b>	NP
<b>Description</b>	UN1210, PRINTING INK, 3, III, (24°C C.C.)

**15. Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

Contact supplier for inventory compliance status

\*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
C.I. Pigment Blue 15 - 147-14-8	1.0
Copper - 7440-50-8	1.0
Xylene - 1330-20-7	1.0

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
C.I. Pigment Blue 15 147-14-8	-	X	-	-
Copper 7440-50-8	-	X	X	-
Xylene	100 lb	-	-	X

1330-20-7			
-----------	--	--	--

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Ethyl acetate 141-78-6	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Copper 7440-50-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

**US State Regulations****California Proposition 65**

The classification listed below only applies to respirable Titanium dioxide and respirable carbon black. This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Carbon black - 1333-86-4	Carcinogen
Quartz - 14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethyl acetate 141-78-6	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Carbon black 1333-86-4	X	X	X
Iron oxide 1309-37-1	X	X	X
C.I. Pigment Blue 15 147-14-8	X	-	X
Silicon dioxide 7631-86-9	-	X	X
Copper 7440-50-8	X	X	X
Xylene 1330-20-7	X	X	X
Quartz 14808-60-7	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. Other information****NFPA**

Health hazards 2

Flammability 3

Instability 0

Special hazards -

**HMIS**

Health hazards 2

Flammability 3

Physical hazards 0

Personal protection X

Chronic Hazard Star Legend

\* = Chronic Health Hazard

Chronic Hazard Star Legend

\* = Chronic Health Hazard

**Key or legend to abbreviations and acronyms used in the safety data sheet**Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

**Key literature references and sources for data used to compile the SDS**

U.S. Environmental Protection Agency ChemView Database  
 European Food Safety Authority (EFSA)  
 EPA (Environmental Protection Agency)  
 Acute Exposure Guideline Level(s) (AEGl(s))  
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
 U.S. Environmental Protection Agency High Production Volume Chemicals  
 Food Research Journal  
 Hazardous Substance Database  
 International Uniform Chemical Information Database (IUCLID)  
 Japan GHS Classification  
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
 NIOSH (National Institute for Occupational Safety and Health)  
 National Library of Medicine's ChemID Plus (NLM CIP)  
 National Toxicology Program (NTP)  
 New Zealand's Chemical Classification and Information Database (CCID)  
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications  
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program  
 Organization for Economic Co-operation and Development Screening Information Data Set  
 World Health Organization

**Issuing Date** 01-Nov-2022

**Revision Date** n/a

**Revision Note**

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**